

TB-NVR9600 Series			
Model	TB-NVR9664	TB-NVR96128	
	OS	Embedded Linux	
Video&Audio input	Bidirectional Talk	1CH,BNC(Line in,2Vp-p,1Kohms)	
	Incoming bandwidth	256Mbps (Up to 64CH 1080P@4M)	
	IPC Input	64CH	
Video&Audio output	VGA	1CH,1920×1080,1280×1024,1280×720,1024×768	
	HDMI	Standard 1.4	
	Audio Output	1CH,BNC(Line out,2Vp-p,300ohms)	
Video&Audio encoding	Audio Compression	G.711A	
	Audio Bit Rate	64Kbps	
Video&Audio decoding	IP channel Resolution	Main stream:Up to 5632×4224 Auxiliary stream:D1	
	Video decoding	MPEG-4/H.264(Up to High Profile@Level5.0)	
	Audio decoding	G.711A/G.726	
	Synchronous Playback	Up to 16CH	
Other Function	Bidirectional Talk	Two-way voice intercom function	
	Motion Detection	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)	
	Picture Capture	Support JPEG Capture	
HDD Interface	SATA	16 SATA Interfaces	
	eSATA	1 eSATA Interface	
	Max Capacity	Unlimited	
External Interface	Network Interface	2 RJ45 10M/100M/1000M self-adaptive Ethernet interfaces	
	USB	2 USB2.0 Interfaces	
	Alarm Input		16CH
			Open/Closed Relay
	Alarm Output		4CH
			NO/NC
	RS-232	1 RS-232 interface	
RS-485	1 RS-485 interface		
Structure	Size	3U,437*483*143mm	
	Weight	18Kg(without HDD)	
	Installation	Rack installation, Desktop installation	
General	Power Supply	110V~220V±10%, 47Hz~63Hz	
	Working Temperature	-10℃--+55℃	
	Working Humidity	10%--90%	
	Consumption	30W(without HDD)	

