

TB-NVR2200 Series					
Model		TB-NVR2204	TB-NVR2208	TB-NVR2216	
OS		Embedded Linux			
Video&Audio input	Incoming bandwidth	32Mbps (Up to 4CH 1080P@8M)	48Mbps (Up to 8CH 1080P@6M)	64Mbps (Up to 16CH 1080P@4M)	
	IPC Input	4CH	8CH	16CH	
Video&Audio output	VGA	1CH,1920×1080,1280×1024,1280×720,1024×768			
	HDMI	1.4a			
		3840×2160,1920×1080,1280×1024,1280×720,1024×768			
Audio Output	1CH,RCA(Line out,2Vp-p,300ohms)				
Video&Audio encoding	Audio Compression	G.711A			
	Audio Bit Rate	64Kbps			
Video&Audio decoding	IP channel Resolution	Main stream:Up to 4096*3072 Auxiliary stream:D1			
	Video decoding	H.265 (Main Profile@L5.0 High-tie) /H.264 Up to High Profile@Level5.0)			
	Audio decoding	G.711A/G711U/ACC			
	Synchronous	4CH	8CH	16CH	
	Decoding Ability	4CH 1080P@30FPS	4CH 1080P@30FPS	4CH 1080P@30FPS	
Elligent Analysis		1CH Face detection or 2CH Perimeter detection	1CH Face detection or 2CH Perimeter detection	1CH Face detection or 2CH Perimeter detection	
		Up to 1080P	Up to 1080P	Up to 1080P	
Other Function	Bidirectional Talk	Two-way voice intercom function			
	Motion Detection	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)			
	Picture Capture	Support JPEG Capture			
HDD Interface	SATA	1 SATA Interface			
	Max Capacity	Unlimited			
External Interface	Network Interface	1 RJ45 10M/100M self-adaptive Ethernet interface			
	USB	1 USB2.0 Interface, 1 USB3.0 Interface			
Structure	Dimensions	250*355*55mm			
	Size	215*215*50mm			
	Weight	1.7KG			
	Installation	Desktop Installation			
General	Power Supply	DC 48V 1.35A	DC 48V 1.35A	DC 48V 1.35A	
	Working	-10℃--+55℃	-10℃--+55℃	-10℃--+55℃	
	Working Humidity	10%--90%	10%--90%	10%--90%	
	Consumption	7W(without HDD)	7W(without HDD)	7W(without HDD)	