

NVR200S Series				
Model	TB-NVR204SC	TB-NVR204SL	TB-NVR208SL	
OS		Embedded Linux		
Video&Audio input	Incoming bandwidth	32Mbps	48Mbps	48Mbps
	Outgoing bandwidth	32Mbps	48Mbps	48Mbps
	IPC Input	4CH	4CH	8CH
	Bidirectional Talk	N/A	1CH,RCA(Line in,2Vp-p,1Kohms)	
Video&Audio output	CVBS	N/A	1CH,BNC(1.0Vp-p,75ohms)	
	VGA	1CH,1280×1024,1280×720,1024×768	1CH,1920×1080,1280×1024,1280×720,1024×768	
	HDMI	Standard 1.3a		
		1280×1024,1280×720,1024×768	1920×1080,1280×1024,1280×720,1024×768	
	Audio Output	N/A	1CH,RCA(Line out,2Vp-p,300ohms)	
Video&Audio encoding	Audio Compression	N/A	G.711A	
	Audio Bit Rate	N/A	64Kbps	
Video&Audio decoding	IP channel Resolution	Main stream:up to 1920x2048 Auxiliary stream:D1		
	Video decoding	MPEG-4/H.264(Up to High Profile@Level4.2)		
	Audio decoding	G.711A/G.726		
	Synchronous Playback	Up to 4CH		Up to 8CH
	Decoding Ability	4CH 720P@30 or 2CH 1080P@30	4CH 720P@30 or 2CH 1080P@30	4CH 720P@30 or 2CH 1080P@30
Other Function	Bidirectional Talk	N/A	Two-way voice intercom function	
	Motion Detection	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)		
	Picture Capture	Support JPEG Capture		
HDD Interface	SATA	1 SATA Interface		
	Max Capacity	Unlimited		
External Interface	Network Interface	1 RJ45 10M/100M self-adaptive Ethernet interface		
	USB	2 USB2.0 Interfaces		
Structure	Dimensions	250*355*55mm		
	Size	1U,215*215*50mm		
	Weight	0.8Kg(without HDD)		
	Installation	Desktop Installation		
General	Power Supply	DC +12V 2A		
	Working Temperature	0℃-- +45℃		
	Working Humidity	10%--90%		
	Consumption	5W(without HDD)	5W(without HDD)	8W(without HDD)